

CARATTERISTICHE TELAIO

FIBRA DI CARBONIO 4 TIPOLOGIE:

1. T800HB/30T/TORAY

2. T700SC/24T/TORAY

3. TR 50S /24T/MITSUBISHI

4. 3K /TORAY

SERIE STERZO SEMINTEGRATA

DA 1"1/8 1"1/2

DIAMETRO TUBO SELLA 27,2 MM

DOPPIO PORTABORRACCIA

REAR TROUGH AXLE BOOST 12 X 148

SCATOLA MOVIMENTO PRESS FIT 30

PESO 1250 GR. (+/-5%)

SF29 CARBON+BOOST

ULTRA



COMPONENTI

TELAIO	SF 29 CARBON + BOOST	ATTACCO MANUBRIO	RITCHEY WCS
FORCELLA	ROCK SHOX SID RL 29" [27,5+] DIFFUSION BLACK	PIEGA MANUBRIO	RITCHEY WCS RIZER 74 MM
AMMORTIZZATORE	ROCK SHOX ARIO	REGGISSELLA	SC + BLACK 27.2
SERIE STERZO	RITCHEY LOGIC 1"1/8 1"1/2	SELLA	SELLE SAN MARCO ERA WIDE OPEN
CAMBIO	SRAM X01 EAGLE BLACK 12	RUOTE	RUOTE SC + MT4B 1690 GR.
COMANDI DX	SRAM TRIGGER X01 EAGLE BLACK 12	COPERTURE	SCHWALBE ROKET RON 29 X 2.25 TR/MAXXI CROSSMARK 29 X 2.25 TR NERO-PARA
FRENI/LEVE	SRAM LEVEL ULTIMATE 180 ANT 160 POST	CAMERA	CST 29 X 1,95 VALVOLA 48 MM
DISCHI	SHIMANO SMRT86 180 MM 160 MM	MANOPOLE	RITCHEY TRUE GRIP I
GUARNITURA	SRAM X01 EAGLE BLACK BB30 32 DENTI	PEDALI	ALLUMINIO
CASSETTA	SRAM X-GLIDE 1295 BLACK 10-50 12	RAPPORTI	12
CATENA	SRAM PC X01 EAGLE BLACK 12	COLORI	CARBON-FUXIA-CYAN MATT • CARBON-GREEN -YELLOW MATT

OPTIONAL

RUOTE SC + MT4B CARBON | TRITTICO RITCHEY WCS CARBON | ATTACCO BULLMOOSE RITCHEY

MISURE	ALTEZZA CF	LUNGHEZZA BOLLA	TUBO STERZO	ANGOLO TUBO SELLA	ANGOLO STERZO
M	445	600	105	73,8°	68°
L	483	620	120	73,8°	68°
XL	520	650	135	73,8°	68°